

## Diginnova Outdoor Advertising Signage


High Brightness, Water Proof Kiosk



### Suitable For:



### Product Highlights:



### Key Features:

- Full HD/UHD options, IPS 65 weather proof
- High brightness - 1000 to 4000 Nits
- Sunlight readable, Steel / Aluminum enclosure
- Tempered glass protection
- Touch / Non touch operation

### Advantages:

- Anti reflective screen, Vandal proof
- 24/7 operation, Full outdoor production
- CMS, Cloud / Remote software
- Auto brightness control, Single/Dual side
- Size: 43" - 75", Temperature control
- Dual side also available

## Technical Data:

Model	DI OFS 43	DI OFS 55	DI OFS 65	DI OFS 75
Display size (TFT LED)	43"	55"	65"	75"
Resolution	1920x1080 FHD & 3840x1920 UHD			
Display area (mm)	941x529	1210x680	1428x803	1681.4x961.2
Panel	Original Full New 100% A+ Grade Brand Panel			
Display ratio	16:09			
Viewing angle	178°/178°(H/V)			
Color	12ms			
Response time	1500 - 3000 nits			
Brightness	4000:1			
Contrast	8 ohm/5watts x 2 pcs			
Speakers (optional)	Built in speakers 8 ohm/10watts x 2 pcs			
Micro Controller	Yes	Yes	Yes	Yes
<b>Power</b>				
Lightning protection grade	Yes			
Leakage protection	30 mA, 0.1 S			
Timing switch	Auto on / off by hour / day / week.			
Input voltage	AC 200 V± 10%,50 / 60 HZ			
Max power consumption (w)	450	800	1150	1500
<b>Encloser</b>				
IP rating	IP 55 & IP 65			
Encloser material	Galvanized steel+zinc powder coating+fine grain powder triple coating.			
Encloser lifetime	5 years, fully outdoor. No color-fading, paint-shedding, rusting.			
Glass type	Tempered glass with AR coating.			
Glass characteristics	Transmissivity > 93%, Reflectivity < 2%			
Unit Dimensions (mm)	730 x 280 x 1850	880 x 280x 2250	1000 x 280 x 2300	1380 x 350 x 2850
Bazel width (mm)	100			
Weight	TBC			
<b>Operating system</b>				
Operating system	Android 5.1 / 7.1			
Processor	Cortex A17 1.8GHz Quad cores Arm, RK3288			
RAM	DDR3 2GB			
ROM	eMMC flash 8GB, (16/32 GB optional )			
<b>CMS software functions</b>				
Rolling subtitles	Display subtitles at any location of the screen with video or image playing.			
Power-off memory	Support replaying from the setting time before power failure			
Split screen	Support 1080P video.1080P picture, video, subtitles and web page split screen function			
Software update	Remote update /USB updating			
Display mode	Support landscape & portrait display			
Play mode	Repeat all, single repeat, order play			
<b>Inputs USB 2.0 x 2, HDMI (output), RJ-45, SD, 3G (optional)</b>				
	Yes	Yes	Yes	Yes
<b>File support</b>				
Video	H.264, MKV, WMV9, MPEG 1/2/4, HD Divx, Xvid, RM/RMVB			
Image	BMP/PNG/GIF/JPEG			
Audio	MP3,WMA,WAV,EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC, APE, BSAC			
Scrolling	Text			
LAN	RJ45 Port, 10/100M Ethernet			
WiFi	Built-in WiFi 802.11B/G/N			
3G (optional)	WCDMA			
<b>Environment</b>				
Operating environment	Exposure to direct sunlight, rain, snow and dust, cooling fan, air conditioning operation			
Operating temperature	40°C ~ +50°C			
Operating humidity	5% ~ 98%			
Operating altitude	≤ 2000 m			
Available colors	Available colors: BLACK (RAL 9005) , DARK GARY (RAL 7043)			