

OUTDOOR


**DIGINNOVA**  
Solutions Galore

## Diginnova Outdoor Advertising Signage


Wall Mount with High Brightness Solution



### Suitable For:



### Product Highlights:



### Key Features:

- Full HD/UHD options, IPS 65 weather proof
- High brightness - 1000 to 4000 Nits
- Sunlight readable, Steel / Aluminum enclosure
- Tempered glass protection
- Touch / Non touch operator

### Advantages:

- Anti reflective screen, Vandal proof
- 24/7 operation, Full outdoor production
- CMS, Cloud / Remote software
- Auto brightness control, Single/Dual side
- Size: 32" - 75"

## Technical Data:

Model	DI OWM 32	DI OWM 43	DI OWM 55	DI OWM 65	DI OWM 75
Display size (TFT LED)	32"	43"	55"	65"	75"
Resolution	1920x1080 FHD			3840x1920 UHD	
Display area (mm)	698 x 392	941 x 529	1210 x 680	1428 x 803	1681.4 x 961.2
Panel	Original Full New 100% A+ Grade Brand Panel				
Display ratio	16:09				
Viewing angle	178°/178°(H/V)				
Color	1.07B, 105%				
Backening defect free	Up to 110°C				
Brightness (nits)	4000 nits		3500 nits		
Contrast	4000:1				
Brightness control	Sensor built-in				
Power					
Lightning protection grade	Yes				
Leakage protection	30 mA, 0.1 S				
Timing switch	Auto on / off by hour / day / week.				
Input voltage	AC 200 V± 10%,50 / 60 HZ				
Max power consumption (w)	450	800	800	1150	1500
Operting system Optional external Media Player IP67					
Operating system	Android 5.1 / 7.1				
Processor	Cortex A17 1.8GHz Quad cores Arm, RK3288				
RAM	DDR3 2GB				
ROM	eMMC flash 8GB, (16/32 GB optional )				
CMS software functions					
Rolling subtitles	Display subtitles at any location of the screen with video or image playing.				
Power-off memory	Support replaying from the setting time before power failure				
Split screen	Support 1080P video.1080P picture, video, subtitles and web page split screen function				
Software update	Remote update /USB updating				
Display mode	Support landscape & portrait display				
Play mode	Repeat all, single repeat, order play				
Connectivity					
HDMI In	X1				
Power port	X1				
SD	X1				
3G (optional)	X1				
File support					
Video	H.264, MKV, WMV9, MPEG 1/2/4, HD Divx, Xvid, RM/RMVB				
Image	BMP/PNG/GIF/JPEG				
Audio	MP3,WMA,WAV,EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC, APE, BSAC				
Scrolling	Text				
LAN	RJ45 Port, 10/100M Ethernet				
WiFi	Built-in WiFi 802.11B/G/N				
3G (optional)	WCDMA				
Environment					
Tempered glass	Anti-Reflective Glass with IK10 Impact-resistant				
Weatherproof design	IP55 - IP67 options				
Cooling system	Fanless + Fliterless, Air conditioner option				
Operating temperature	-30°C ~ 55°C				
Operating humidity	5% ~ 98%				
Operating altitude	≤ 2000 m				
Available colors	Available colors: BLACK (RAL 9005) , DARK GARY (RAL 7043)				
Unit weight (kg)	25	55	60	96	120
Unit Dimension (mm)	750x450x126	1040x691x91.5	1268x737x125.5	1525x900x91.5	1708x982x130

Images used are all for illustrative purpose only. The technical specification & product appearance may change based on actual product offered by the company. Terms & conditions apply.