

## Technical Data:

Panel Information	
Display size	21.5" commercial LED display screen
Resolution	1920x1080 FHD +I4
Panel	Original Full New 100% A+ Grade Brand Panel
Display ratio	16:09
Viewing angle	178°/178°(H/V)
Color	16.7M
Brightness	26nits
Contrast	1500:1
Touch	(PCAP touch optional)
Speakers	Built in speakers 8 ohm/5watts x 2 pcs
General Information	
Operation system	Android 7.1.2
Processor	Cortex A17 1.8GHz Quad cores Arm, RK3288
RAM	DDR3 2GB,
ROM	eMMC flash 8GB
Functions	
Rolling subtitles	Display subtitles at any location of the screen with video or image playing.
Power-off memory	Support replaying from the setting time before power failure
Split screen	Support 1080P video,1080P picture, video, subtitles and web page split screen function
Software update	Remote update /USB updating
Display mode	Support landscape & portrait display
Play mode	Repeat all, single repeat, order play
Supported Infrared Sensor to Detect Body Temp	
Software	Software to detect temp with voice reading
Type of sensor	Infrared sensor, Thermal imaging (Customized & optional)
Empty tank notification	Hand Sanitizer liquid Status & alarm
Camera	Build USB web camera in the top of the screen (Set aside for face ID)
Face recognition	Fast Face recognition for both masked and unmasked people Support register and record information Support recorded data output and API
Media Playing	
Support video format	AVI (H.264) DIVX DIVX, XVID, rm rmvb, MKV (H.264, DIVX, DIVX, XVID), WMV, MOV MP4 (H.264, MPEG, DIVX, XVID), DAT (VCD format), VOB (DVD format), PMP, MPEG, .MPG, FLV (H.263, H.264), ASF, TS, TP, 3GP, MPG. Etc
Support image format	BMP, PNG, GIF, JPEG.
Support audio format	MP3, WMA, MP2, OGG, AAC, M4A, MA4, FLAC, APE, 3GP, WAV.
Input Ports	
	USB 2.0 X2, HDMI output X1, SD X1, RJ45 X1, WiFi 802.11b/g/n, 3G/4G SIM Slot (opt) X1
Power Supply	
	Power Input: AC 100-240V   Power Supply: Industrial High-Level Power module AC100~240V 50/60 HZ Max. power cosumption: 50W   Standby power consumption: <3 W
Connectivity	
	LAN: 10/100M RJ45 port   WIFI: 2.4GHz WiFi standard, 5GHz WiFi optional 3G / 4G cellular network (optional): WCDMA/TD-LTE/FDD-LTE
Temperature	
	Working Temperature: 0°C-50°C   Storage Temperature: -20°C-60°C
Software & Languages	
CMS Software	CMS Software Provide with free cloud service API Supporting
Suitable for	Spray, Soap/Gel, Foam Supported, offer one of them
Languages OSD	Multi-Language Body Temperature Display on Screen:(English, Italy, Spain, Portugal, German, French, polish, Russian, Arabic, Chinese)
Languages & Voice Speech	Multi-Language Body Temperature Voice Speech:(English, Italy, Spain, Portugal, German, French, polish, Russian, Arabic)
Other Information - Outer Kiosk Structure	
	Metal case, Color white, Mounting way - wall mounted & floor standing. Adjustable height, Main outer shell is made by extra quality Iron material. With a protection layer of high-penetrating Tempered glass (with 3mm-4mm thickness) on the surface of the LCD Panel. The outer surface finish with commercial grade of powder coating with an anti-wear texture.
Safety	
Certification	CE ROHS
Accessories	Remote control, key, wall mounted bracket, floor stand, screws, Wifi antenna& power cable
Warranty	1 year
Packing	Honeycomb export packing
Dimension	1620x250x550mm
Weight	35kg

Images used are all for illustrative purpose only. The technical specification & product appearance may change based on actual product offered by the company. Terms & conditions apply.

## INDOOR

**DIGINNOVA**  
Solutions Galore

## Diginova Hand Sanitizing with Digital Signage

Hand Sanitizer, Instant Temperature & Face Mask Detection



### Suitable For:



### Product Highlights:



### Key Features:

- 21.5" commercial display screen
- 24x7 operation, Android 7.1, Built-in media player
- Built-in Infrared thermometer sensor
- 2GB/8GB memory
- Auto dispense, Touch free, Big storage - 2Ltr capacity

### Advantages:

- Hand sanitizer
- Face mask, Temperature detection
- Digital signage display
- CMS software to publish content
- Wall mount / Floor standing display

## Customization

### 21.5" Hand Sanitizing LCD Digital Signage



### Size Dimensions



- Spray, Soap/Gel, Foam Supported
- Brightness: 300 - 1000 Nits
- Body Temperature Display on Screen
- Body Temperature Voice Speech
- Cloud Service of CMS
- Face Recognition Recording
- Body Temperature Testing
- Multi-Language

